



Icarus

35.13



*macchine edili ed agricole*  
**d DIECI**  
S.r.l.



## PERFORMANCES

Maximum capacity:	3.500 kg
Capacity at maximum height with stabilizers:	3.500 kg
Capacity at maximum height on tyres:	2.500 kg
Maximum capacity boom with stabilizers:	1.000 kg
Maximum capacity boom on tyres:	350 kg
Maximum lifting height:	12,90 m
Maximum horizontal boom extension:	9,10 m
Boom at maximum height:	1,10 m
Angle of fork arching:	134°
Tearing force:	5.700 daN
Towing force:	7.300 daN
Maximum slope for overtaking:	40 %
Total empty weight:	10.600 kg
Max speed:	30 km/h

(on request 40 km/h with TA engine)

## TRANSMISSION

Transmission: hydrostatic with variable capacity pump  
 Hydraulic engine: with automatic change  
 Gear reversing: electro - hydraulic  
 Inching pedal for controlled forward movement  
 2 speed power steering.

## HYDRAULIC CIRCUIT

Gear pump with capacity at speed: 100 l/min  
 Max working pressure: 230 bar  
 Distributor controls with joystick: 3 in 1

## DIFFERENTIAL AXLES

Steering axles: 2, with epicycloidal reduction gears  
 Type of steering: 4 wheels / transversal / 2 wheels  
 Front axle: rigid (levelling on request)  
 Rear axle: oscillating  
 Service braking: oil bath on the 4 wheels with split system

## ENGINE

ENGINE IVECO NEF F4GE0454A - TC - 74 kW  
 Maximum power: 74 kW (102 hp) at 2300 rpm  
 Operating principle: four-stroke engine, diesel  
 Cylinders number and layout: 4, vertical in line  
 Displacement: 4485 cm<sup>3</sup> - Turbo compressor  
 Cooling system: liquid

ENGINE IVECO NEF F4GE0484C - TA - 94 kW  
 Maximum power: 94 kW (128 hp) at 2300 rpm  
 Operating principle: four-stroke engine, diesel  
 Cylinders number and layout: 4, vertical in line  
 Displacement: 4485 cm<sup>3</sup> - Aftercooler turbo compressor  
 Cooling system: liquid

## REFUELLING (litre)

Hydraulic circuit: 160  
 Fuel tank: 105

## STANDARD DEVICES

Anti-tipping device with block for hazardous movements.  
 Stabilizers with independent hydraulic tilting.  
 Closed soundproof homologated cab ROPS - FOPS, with heating.  
 Hydraulic socket for possible accessories on boom head.  
 Front self-locking axle (limited slip 45%).

## TYRES

Tyres: 16/70x20" MPT04  
 Alternative: 405/70x24" MPT04

## OPTIONAL AND ACCESSORIES

Optional and Accessories: see the relevant catalogue

The information contained in the present publication are only intended as an indication; the models described may be modified, without notice, by the manufacturer. Drawings and photographs may refer to optional equipment or to particular specifications for other countries. For any further information, please contact DIECI headquarters at the address given below.